AMENDMENTS TO THE SPECIFICATION

Please amend the following paragraph at page 8, line 23 to page 9, line 8 as follows:

Returning to Figs. 5A-5C, the outer housing 17 of the caster assembly 16 is connected to a downwardly extending outer wall ~~15~~ 53 that extends substantially parallel to the outer wall 15 of the tank 11 as shown. The outer wall 53 of the caster housing 17 terminates or is connected to a u-shaped lower edge shown at 54. The u-shaped lower edge 54 is disposed between and connected to the outer wall 53 and an inner wall 55. In the preferred embodiment shown in Figs. 5A-7C, the inner wall 55 extends upward in a substantially parallel manner to and in a budding engagement with the inner wall 51 of the tank 11. The inner wall 55 of the caster housing 17 also, in the preferred embodiment shown, terminates at a radially inwardly extending lip 56 that is parallel to and in a budding engagement with the bottom panel 23 of the cylindrical tank 11. Further, the outer wall 53 of the caster housing 17 is also preferably connected to a radially inwardly extending ledge 57. The radially inwardly extending ledge 57, the u-shaped lower edge 54 and the upwardly extending inner wall 55 of the caster housing 17 forms a female receiving area for receiving the lower bead 22 of the tank 11. When the lower bead 22 is firmly inserted into the female receiving area defined by the ledge 57, the u-shaped lower edge 54 and the inner wall 55 of the caster housing 17, the ledge 57 snaps over the top wall 58 (see also Fig. 7C) of the bead to provide a snap-fit connection. Also shown in Figs. 5A-7C are the outer edges shown at 61 of the caster housings 17 and wheel dolly housing 40 which extend over the bead 22 and provide a reinforcing rib to the snap-fit connection.